EB-L1715S

DATASHEET





Versatile 15,000-lumen 3LCD laser projector, offering outstanding fit and forget reliability as well as sharp, vivid imagery with SXGA+ resolution.

Exceptionally bright 15,000-lumen SXGA+ performance combines with rich, vivid colours to make the EB-L1715S installation laser projector an ideal option for large rooms and venues. As well as reliable fit and forget performance, it offers very flexible installation, creating a dedicated solution for scenarios where only maximum performance and durability will do.

Laser-sharp images

Ensure that your presentations, images and video pack a punch with the vivid, sharp projection offered by this 3LCD laser projector. Designed for larger venues, its high resolution SXGA+ images are vivid and bright, even in daylight, while inorganic phosphor wheel technology provides superior light and heat resistance to deliver excellent reliability that lasts for up to 83,000 hours¹.

Flexible positioning

Thanks to a wide range of motorised lenses, including optional ultra-short-throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image. The projector also has a built-in camera to ensure accurate calibration and capture diagnostic images (this can be fully disabled to prevent remote access).

Versatile new software

All models in the EB-L1000 series can take advantage of free Epson Professional Projector Tool software from December 2017. It allows you to set up multiprojector installations straight out of the box, simply and quickly, as well as utilising advanced techniques such as projection-mapping and edge-blending. **Quick set-up**

Get started quickly thanks to a lens memory function which stores projector settings such as image position, focus and zoom, for prompt access when projecting images in different aspect ratios, or using different lenses.

KEY FEATURES

- Laser light source technology Outstanding brightness and colour, with fit and forget reliability
- Sharp, clear imagery Outstanding clarity and detail for crisp images and readable text
- Versatile new software Set up multiple projector installations and utilise advanced projection techniques
- Flexible 360° installation True flexibility without distortion or loss of brightness
- Added peace of mind Product comes with five-year, 20,000hour warranty





PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology	
LCD Panel	1,06 inch with C2 Fine	
IMAGE		
Colour Light Output	15.000 lumen- 10.500 lumen (economy) In accordance with IDMS15.4	
White Light Output	15.000 lumen - 10.500 lumen (economy) In accordance with ISO 21118:2012	
Portrait Colour Light Output		
Portrait White Light Output	Dutput 15.000 lm	
Resolution	SXGA+ (1400 x 1050), 4:3	
Contrast Ratio	2.500.000 : 1	
Native Contrast	2.000 : 1	
Keystone Correction	Manual vertical: ± 45 °, Manual horizontal ± 30 °	
Colour Reproduction	Upto 1.07 billion colours	
OPTICAL		
Projection Ratio	1,62 - 2,65:1	
Zoom	Motorized, Factor: 1 - 1,6	
Lens position memory	10 positions	
Image Size	60 inches - 500 inches	
Projection Distance Wide	1,9 m - 16,7 m	
Projection Distance Tele	3,2 m - 27,1 m	
Projection Distance Wide/Tel		
Projection Lens F Number	1,8 - 2,3	
Focal Distance	36 mm - 57,35 mm	
Focus	Motorized	
CONNECTIVITY Interfaces	Starse mini isak audia in (20) Starse mini isak audia aut. UDDaseT, DNC in, UDM in, DV/ in	
internaces	Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in,	
	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B	
Francis Ducing the Arm	(Service Only), Wireless LAN b/g/n (2.4GHz) (optional)	
Epson iProjection App	Ad-Hoc / Infrastructure	
ADVANCED FEATURES		
Security	Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password	
	protection	
Features	Absolute Black, Auto calibration, Customizable user logo, Frame interpolation, Integrated	
	camera for image calibration & image capture, Lens position memory	
Video Colour Modes	Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709	
GENERAL		
GENERAL Energy Use	1.024 W, 647 W (economy), 0,3 W (standby), On mode power consumption as defined in JBMS 84 938 W	
Energy Use	84 938 W	

LOGISTICS INFORMATION

SKU	V11H890140
EAN code	8715946645988
Dimensions Single Carton	738 x 771 x 320 mm
Carton Weight	34,38 Kg
Country of Origin	China

EB-L1715S

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- VGA cable
- Cable cover
- CD Manual

OPTIONAL ACCESSORIES

- 3D Polarizer ELPPL01 V12H618A01
- Air Filter ELPAF51 V13H134A51
- Ceiling Mount ELPMB47 Low EB-G7000/L1000 V12H802010
- Ceiling Mount ELPMB48 High EB-G7000/L1000 V12H803010
- HDBaseT Transmitter ELPHD01 V12H547040
- Quick Wireless Connect USB key ELPAP09 V12H005M09
- Stacking Frame ELPMB50 L1000 Series (Premium) V12H003B50
- Wireless LAN Adapter ELPAP10 V12H731P01

OPTIONAL LENSES

- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLM09 Mid throw 2 G7000/L1000 series
- V12H004M09
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLM11 Mid throw 4 G7000/L1000 series
- V12H004M0B
- Lens ELPLM15 Mid Throw L1500/L1700 Series V12H004M0F
- Lens ELPLU03 G7000 & L1000 Series ST off axis
- V12H004U03
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1
- V12H004W05
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06

1. - Laser life of up to 83,000 hours in custom mode.

